

SHEATHING OVER  
16GA. (1.5mm) (MIN.)  
STEEL STUD FRAMING  
(BY OTHERS)  
SPACED 16" (400mm) O.C. MAX.

FACTORY ATTACHED  
INTERLOCKING  
CHANNEL

FIELD ATTACH JOINT  
CHANNEL MATE THRU  
SHEATHING AND INTO  
EACH STUD W/ #10 (5mm) TEK  
SCREWS AS REQ'D.

USE BUILDDEX "MAXISEAL"  
W/ NEOPRENE WASHER  
OR APPROVED EQUAL

AT CONC./CMU WALLS -  
USE COATED TAP-CONS  
W/ NEOPRENE WASHER

SEALANT AND  
BACKER ROD  
(BY OTHERS - TYP.)

FACTORY ATTACHED  
JOINT CHANNEL

**StoneLite**<sup>®</sup> PANEL

VAPOR  
BARRIER  
SHEET  
(INSTALLED  
BY OTHERS)

WINDLOAD AND  
BEARING  
APPLICATION

WINDLOAD  
APPLICATION

1 7/8" (48mm)  
MIN. SHIM AS  
REQ'D.

SP-4

NARROW INTERLOCKING JOINT CHANNEL

**Stonepanels**  
INTERNATIONAL LLC

2400 HWY 1431 WEST  
Marble Falls, TX 78654  
800.328.6275  
www.stonepanels.com